MOUNTING FRAME INSTALLATION

- 1. SEE INSTALLATION INSTRUCTIONS RECEIVED WITH HYDRATION STATION AND HCR8 FOR ADDITIONAL PERTINENT INFORMATION. FOR ROUGH-IN, USE THE APPROPRIATE DIMENSIONS SHOWN.
- 2. HOLD ROUGH-IN DIMENSIONS ±1/8" (3.2mm).
- 3. WHEN INSTALLING THIS UNIT LOCAL, STATE OR FEDERAL CODES SHOULD BE ADHERED TO.
 FOR DIFFERENT INSTALLATION HEIGHTS OTHER THAN SHOWN, DIMENSIONS MARKED (*) MUST BE ADJUSTED ACCORDINGLY.
- 4 ALIGN HOLES IN CHILLER SUPPORT TRAY WITH HOLES IN FRAME AND FASTEN IN PLACE WITH #10 SHEET-METAL SCREWS SUPPLIED WITH UNIT.
- 5. USE NSF-61 3/8" OD TUBING WITH SUFFICIENT PRESSURE RATING TO CONNECT CHILLER AND HYDRATION STATION.
- 6 TO ATTACH GRILLE TO MOUNTING FRAME, SLIDE 6-32 U-NUTS (SUPPLIED), THREADED PORTION INWARD, OVER MOUNTING TABS ON FRAME. PLACE GRILLE OVER FRAME AND INSERT 6-32 SCREWS (SUPPLIED) THROUGH SLOTS IN SIDE OF GRILLE AND SCREW INTO U-NUTS.



