



# model MTGFR.SM

Mounting Frame

## FEATURES & BENEFITS

### CONSTRUCTION

Constructed of heavy gauge galvanized steel, this frame provides the needed support for Haws single bubbler drinking fountains along with added corrosion resistance for long life.

### MOUNTING

Normally mounted in advance, this frame allows for precise mounting and superior finish when aesthetics is a must.

## OPTIONS

To see all options for this model, visit [www.hawesco.com](http://www.hawesco.com)





## SPECIFICATIONS

Model MTGFR.SM mounting frame is made of heavy gauge galvanized steel with pre-punched mounting holes and is used with Haws single bubbler electric fountains.

## APPLICATIONS


Haws produces mounting plates and frames to assist in the installation process as well as to provide solid bases for the wall mounted designed fountains. Mounting plates and frames meet the requirements solely for the specified applicable fountains and are not designed to be used in the installation of any unspecified fountain.





\* IF YOUR FOUNTAIN IS THIS STYLE  
USE THESE DIMENSIONS

A	B
1-3/8" (35mm)	4-7/8" (124mm)



\* IF YOUR FOUNTAIN IS THIS STYLE  
USE THESE DIMENSIONS

A	B
1-3/16" (30mm)	4-11/16" (119mm)

#### CHILLER ELECTRICAL INSTALLATION

1. ENSURE ELECTRICAL POWER IS OFF AND POWER MATCHES VOLTAGE, PHASE AND CYCLE LISTED ON CHILLER LABEL.
2. REMOVE FRONT PANEL TO GAIN ACCESS TO INTERNAL JUNCTION BOX.
3. HARDWIRE CHILLER THROUGH ITS SIDE. WIRE IN ACCORDANCE WITH LOCAL, STATE OR FEDERAL ELECTRICAL CODES.
4. REPLACE FRONT PANEL. **DO NOT** APPLY POWER UNTIL WATER SUPPLY IS CONNECTED **AND** ON.

#### MOUNTING FRAME INSTALLATION

1. THIS FRAME IS USED WITH SEVERAL DIFFERENT MODELS. SEE INSTALLATION INSTRUCTIONS RECEIVED WITH THE FOUNTAIN FOR PROPER LOCATIONS OF 5/16-18 PANEL NUT RETAINERS. FOR ROUGH-IN USE THE APPROPRIATE DIMENSIONS SHOWN ABOVE. WASTE AND SUPPLY HEIGHTS ARE ALSO DETAILED ON THE FOUNTAIN INSTALLATION INSTRUCTIONS.
2. HOLD ROUGH-IN DIMENSIONS  $\pm 1/8"$  (3.2mm).
3. WHEN INSTALLING THIS UNIT LOCAL, STATE OR FEDERAL CODES SHOULD BE ADHERED TO. FOR DIFFERENT INSTALLATION HEIGHTS OTHER THAN SHOWN, DIMENSIONS MARKED (\*) MUST BE ADJUSTED ACCORDINGLY.
4. ALIGN HOLES IN CHILLER SUPPORT TRAY WITH HOLES IN FRAME AND FASTEN IN PLACE WITH #10 SHEET-METAL SCREWS SUPPLIED WITH UNIT.
5. FOUNTAIN REMOVAL: FIRST REMOVE SCREWS AND THEN SQUEEZE CLIPS ON NUT RETAINER TO POP OUT. INSTALL IS REVERSE OF REMOVAL.



INFO FAX : 1-888-FAX-HAWS (1-888-329-4297)  
1455 Kleppe Ln, Sparks NV, 89431  
Phone: 775-359-4712 Fax: 775-359-7424  
Haws Ag Bachweg 3 CH-3401 Burgdorf Switzerland  
Haws Mfg Pte Ltd 74 Sungei Kadut Loop Singapore 729531  
e-mail: Haws@hawsco.com website: www.hawsco.com

ECR NO.	REVISED PER	BY:	MODEL(S):	PART NUMBER:
ECN: 4181	DATE:	VWC	MTGFR.SM	0002080294
DRAWN:	DATE:	CHK'D:	INFO FAX DOC #:	DRAWING NUMBER:
D. ZHOU	08/97		26843776	06650A00
APPROVED:	DATE:	SCALE:	DRAWING TYPE:	SIZE: A
		1:16	INSTALLATION/FAXBACK	1 OF 1